

T401^{EX}



ارتباط مطمئن، حتی در قلب خطر



MIL-810-G

FC CE

Zone 2



مناسب برای:

آتش نشانی

نیروهای امنیتی، نظامی و انتظامی

تیمهای امداد و نجات، عملیات میدانی

پالایشگاه ها، پلیمر، پتروشیمی ها و کارخانجات

معادن و صنایع سنگین نیروگاه ها و پست های برق

و ...



Feature	Technical Description
Main CPU & SW	MTK6761 Quad-Core CPU 2.0GHz ,Support Pin-to-Pin Octa-Core CPU
OS	Android 10
Language	Multi-Language
Memory	RAM 2GB + ROM 16GB (Optional 3GB + 32GB)
SD Card	Up to 32GB
LCD	4 inch
LCD Resolution	854 x 480 dpi
LCD Colors	16M color IPS TFT
Touch Type & Size	G+F+F, Glove Touch Supported
Surface Treatment	Anti-glare
Glass	Gorilla Glass
Multi-Touch	5-Point Multi-Touch
Sensors	G-Sensor, Acceleration Sensor, Proximity Sensor, Light sensor
Network / Frequency Bands	GSM: 850/900/1800/1900 – WCDMA: B1/B2/B4/B5/B8 – FDD-LTE: B1/B2/B3/B4/B5/B7/B8/B12/B13/ B17/B20/B28 (A&B)
Cameras	Rear: 8MP with Focus, Front: 5MP Flash light: real light
Wi-Fi	802.11a/b/g/n
Wi-Fi Antenna Type	Wi-Fi & BT Coexistence, 50Ω
Bluetooth	BT v4.0 + BLE / BT2.1 + EDR
BT Power & Range	Class 2, Range up to 10m
GPS	GPS, Beidou , GLONASS
Speaker & Microphone	2.0W Speaker, 116dB SPL, Dual Mic with Noise Reduction, -42dB±3 Sensitivity
SIM Card	Dual Micro-SIM
Vibrator	Yes
USB	Type-C, Above v2.0, OTG Supported
Cable Length	1.0m
Ear jack Interface	M6 Connector
Indicator LED	3 Colors: Red, Green, Blue
Dimensions	142.5 × 72.5 × 25mm
Weight	311g
IP Code	IP68
Drop Test	1.8m Drop Resistance
Keys	Channel Knob, PTT, SOS, Power, Volume, Camera
Battery Type	Li-Po
Battery Capacity	4500mAh with MSDS, UN38.3
Removable Battery	Yes
Charge/Data Interface	Type-C
Cradle Spec	Custom Cradle Supported (5V/3A Output)
Power Adaptor	Input: 100–240V AC, Output: 5V/2A DC, Type-C
Environmental Conditions	Operating: -20~60°C, Storage: -30~70°C, Humidity: 20–90%, ESD Contact ±8KV / Air ±12KV, RoHS 6
Certifications & Safety	CE (Europe), FCC (USA)

Accessories



Bluetooth Button



Desktop Charger



PB001 protective bag



M6 External Camera



ندارسان پیتر

www.nedaresanan.com