

# T610



« امنیت و ارتباط بی‌مرز »  
« در هر مسیر کنار شما »



MIL-810-G  
GMS® FC CE



**مناسب برای:**

- ✓ مراکز فاوا و مخابرات
- ✓ خودروهای امدادی
- ✓ خودروهای آتش نشانی، نظامی و انتظامی
- ✓ کامیون ها و اتوبوس ها و تاکسی های بیسیم
- ✓ فرودگاه‌ها، ترمینال‌ها و قطارها
- ✓ خدمات شهری و شهرداری



| Feature             | Technical Description                                                                                                                                       |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU                 | MTK6739 quad core                                                                                                                                           |
| OS                  | Android 8.1                                                                                                                                                 |
| OS Languages        | Korean, Japanese, English, Chinese...                                                                                                                       |
| Memory              | RAM 2GB + ROM 16GB                                                                                                                                          |
| SD Card             | Up to 64GB                                                                                                                                                  |
| Display             | 5.5 Capacitive active touch panel + touch keyboard<br>1280* 720 DPI                                                                                         |
| LCD                 | 5.5" TFT                                                                                                                                                    |
| Resolution          | 1280 × 720 dpi WVGA                                                                                                                                         |
| Colors              | 16M Color IPS TFT                                                                                                                                           |
| Touch               | 5.5" Capacitive, 5-point Multi-touch                                                                                                                        |
| Glass               | Corning Gorilla Glass 3                                                                                                                                     |
| Sensors             | G-Sensor, Gyroscope, Compass                                                                                                                                |
| Network (EU)        | GSM: 850/900/1800/1900 MHz – WCDMA:<br>B1/B2/B5/B8 – TD-SCDMA: B34/B39 – CDMA2000: BCO<br>– LTE-TDD: B38/B39/B40/B41 – LTE-FDD:<br>B1/B3/B7/B8/B20/B28(A&B) |
| Network (US)        | GSM: 850/1900 MHz – WCDMA: B1/B2/B4/B5 (B19) –<br>LTE-FDD: B1/B2/B4/B5 (B19)/B7/B12 (B17)/B13/B28                                                           |
| DMR                 | UHF 400–470 MHz                                                                                                                                             |
| Camera              | Front: 200M external USB camera DB9 interface<br>support USB camera                                                                                         |
| Wi-Fi               | 802.11a/b/g/n (2.4G & 5G)                                                                                                                                   |
| Wi-Fi Antenna       | Internal FPC, Wi-Fi & BT Coexistence                                                                                                                        |
| NFC                 | Support                                                                                                                                                     |
| Bluetooth           | BT v4.0 + BLE, v2.1 + EDR                                                                                                                                   |
| BT Range            | Class 2, up to 10m                                                                                                                                          |
| GPS                 | Supported                                                                                                                                                   |
| GLONASS             | Supported                                                                                                                                                   |
| Speaker             | Ø50mm, 4Ω, 5W                                                                                                                                               |
| SPL                 | 106dB                                                                                                                                                       |
| Receiver            | 1506                                                                                                                                                        |
| Microphone          | Dual Mic, independent DMR/PoC Mic, -42dB±3                                                                                                                  |
| SIM Card            | 1× Nano SIM (Push type)                                                                                                                                     |
| Vibrator            | Yes                                                                                                                                                         |
| Connector           | DB9 Connector                                                                                                                                               |
| Earjack             | None                                                                                                                                                        |
| LED                 | 3-Color (Red, Green, Blue)                                                                                                                                  |
| Dimensions (H×W×D)  | 190 × 93 × 66 mm                                                                                                                                            |
| Weight              | 486g                                                                                                                                                        |
| IP Code             | IP54                                                                                                                                                        |
| Drop Test           | Standard                                                                                                                                                    |
| Keys                | PTT, SOS, Channel, Power, Volume...                                                                                                                         |
| Battery             | Not Included                                                                                                                                                |
| Data Interfaces     | DB9                                                                                                                                                         |
| External Interfaces | 4-pin GX16 Hand Mic, 12V Power Supply                                                                                                                       |
| DMR Capacity        | 16 Channels                                                                                                                                                 |
| Channel Spacing     | 12.5/25 kHz (Analog), 12.5 kHz (Digital)                                                                                                                    |
| TX Power            | 0.5W / 2W                                                                                                                                                   |
| Operation Distance  | Up to 2km                                                                                                                                                   |
| Frequency Stability | ±0.5ppm                                                                                                                                                     |
| Sensitivity         | 0.22mV (Typical)                                                                                                                                            |
| Operating Temp.     | -20°C ~ 70°C                                                                                                                                                |
| Storage Temp.       | -30°C ~ 80°C                                                                                                                                                |
| Humidity            | 20% ~ 90%                                                                                                                                                   |
| ESD                 | Contact ±6KV, Air ±8KV                                                                                                                                      |
| RoHS                | RoHS 6 Compliant                                                                                                                                            |
| Certifications      | CE (Europe), FCC (USA)                                                                                                                                      |

Suitable for



BUS



Ship Boat



TAXI



Truck Silhouette



Train



ندارسانان پیتر

www.nedaresanan.com